



DECISION GROUP INC.

ADDRESS: 4/F NO. 31, ALLEY 4, LANE 36, SEC 5, MING-SHEN EAST ROAD, TAIPIE, TAIWAN. R.O.C

Tel.: (02)2766-5753 Fax.: (02)2766-5702, 2756-9591

URL: www.decision.com.tw Email: decision@decision.com.tw

APCLeX2RS232SMD PCI Express 2 PORT RS232 CARD



Features:

- ✚ 128-byte deep FIFO per transmitter and receiver.
- ✚ Automated in-band software flow control using programmable Xon/Xoff in both directions.
- ✚ Automated out-of-band hardware flow control using Tx/Rx/RTS/CTS/DSR/DTR/DCD/RI/GND.
- ✚ Compliant with PCI Express base specifications revision 1.1a.
- ✚ High Performance Dual Channel Oxford 950 UART.
- ✚ Native single-Chip, single lane PCI Express.
- ✚ Selectable power output on pin 9 for the serial port.
- ✚ Configurable in 5V, 12V, and RI (non-powered) modes.
- ✚ Two high speed RS-232 serial ports with data transfer rate up to 460.8 Kbps.
- ✚ Ships with half-height mounting bracket; includes optional standard bracket.

Specifications:

Bus Type	PCI Express
Chipset ID	OXFORD-oxpcie952
Number of Ports	2-RS232
Transfer Rate	460.8Kbps
Dimensions	70 (W) x 80 (L) mm
Environment	Operating Temperature: -10°C to 80°C Storage Temperature: -20°C to 100°C
OS Compatibility	Windows2000/XP/2003/Vista/7

** Accessories: 1 x PCI Express RS232 Card, 1 x Driver CD, 1 x Instruction Manual

